

➤ Product Description

ANCHORBOND D2 PVA is a white formulated adhesive based on an aqueous polyvinyl acetate polymer emulsion. The thicker consistency of this adhesive gives good gap filling properties and elasticity. High grab and fast drying PVA adhesive.

➤ Areas of Application

General purpose woodworking adhesive meeting the requirements of BS 4071. Gap filling and high grab properties make it ideal for chair frame manufacture. Can be coloured to a wide range of colours if required.

➤ Bonding Instructions

Adhesive to be applied to a clean, dust and grease free surface at a suitable coating weight to induce maximum bond performance.

Adhesive which has been stored for prolonged periods should be agitated before use.

➤ Technical Data

Description	Value
Solids Content	44%
Viscosity (Brookfield RVT, Spindle 4, Speed 5rpm)	135 poise @ 20°C
Bond Strength	High
Drying Time	Fast
Shelf Life	1 Year

➤ Storage & Handling

Store between 5°C - 25°C.

This product should not be allowed to freeze.

➤ Cleaning

Wash all equipment with water before adhesive dries.

Dried adhesive should be soaked for 24 hours.

➤ Ordering Information

Part Number	Container Size
1001	5kg
1001/4	4 x 5kg
1002	20kg
1003	1000kg
1005	250kg

➤ Health & Safety

ALWAYS READ RELEVANT MATERIAL SAFETY DATA SHEET BEFORE USE.

Data herein is furnished for information purposes only, and is believed to be reliable. Redwood UK Ltd and any subsidiary companies cannot assume responsibility for the results obtained by others, over whose methods it does not control. It is the users' responsibility to determine suitability for the user's intended purpose of any product and any product method mentioned herein, and to adopt any such precautions as may be necessary to protect property and persons against hazards that may be involved in the handling and use thereof. We recommend that each prospective user test the proposed application to determine the suitability of this product for the purpose intended prior to incorporating any product or application in its manufacturing process using this data as a guide. Redwood UK Ltd accept no liability arising out of the use of this information or the products described herein.