

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** PANELWIPE 3 (SLOW)**REACH registered number(s):** 01-2119473851-33**CAS number:** 64742-49-0**EINECS number:** 265-151-9**Index number:** 2020F**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of substance / mixture:** Uses in coatings. Use in cleaning agents. Use in metal working fluids / Rolling oils. Use as a functional fluid. Laboratories. Road and construction applications.**1.3. Details of the supplier of the safety data sheet****Company name:** Leading Solvents
Marston Business Park
Rudgate
Tockwith
York
YO26 7QF
Tel: 01423 358058
Fax: 01423 358923
Email: enquiries@leading-solvents.co.uk**1.4. Emergency telephone number****Emergency tel:** 01423 358058 (Office Hours Only)**Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066**Most important adverse effects:** Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.**2.2. Label elements****Label elements:****Hazard statements:** H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 2

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard pictograms: GHS02: Flame

GHS08: Health hazard

GHS09: Environmental

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P243: Take action to prevent static discharges.

P403+P235: Store in a well-ventilated place. Keep cool.

P331: Do NOT induce vomiting.

P273: Avoid release to the environment.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: HYDROCARBONS,C7-C9,N-ALKANES,ISOALKANES,CYCLICS

CAS number: 64742-49-0

EINECS number: 265-151-9

REACH registered number(s): 01-2119473851-33

Contains: Substance contains less than 0.1%w/w benzene.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues

Ingestion: Wash out mouth with water. Consult a doctor.

[cont...]

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 3

Inhalation: Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid or complete, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

[cont...]

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.
Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Original container stored in a dry and cool place.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

State	Respirable dust			
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200 mg/m ³	-	-	-

Hazardous ingredients:

HYDROCARBONS,C7-C9,N-ALKANES,ISOALKANES,CYCLICS

Workplace exposure limits:

State	Respirable dust			
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200 mg/m ³	-	-	-

DNEL/PNEC Values

PANELWIPE 3 (SLOW)

Type	Exposure	Value	Population	Effect
DNEL	Dermal	773 mg/kg/day	Workers	Systemic
DNEL	Inhalation	2035 mg/m ³	Workers	Systemic
DNEL	Dermal	699 mg/kg/day	Consumers	Systemic
DNEL	Inhalation	608 mg/m ³	Consumers	Systemic

[cont...]

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 5

DNEL	Oral	699 mg/m3	Consumers	Systemic
------	------	-----------	-----------	----------

Hazardous ingredients:

HYDROCARBONS,C7-C9,N-ALKANES,ISOALKANES,CYCLICS

Type	Exposure	Value	Population	Effect
DNEL	Dermal	773 mg/kg/day	Workers	Systemic
DNEL	Inhalation	2035 mg/m3	Workers	Systemic
DNEL	Dermal	699 mg/kg/day	Consumers	Systemic
DNEL	Inhalation	608 mg/m3	Consumers	Systemic
DNEL	Oral	699 mg/m3	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

Hand protection: Acceptable glove barrier materials include: Butyl rubber, Rubber (natural latex), Nitrile rubber, Polyvinyl alcohol (PVA). It should be noted that liquid may penetrate the gloves, frequent changes are recommended.

Eye protection: Safety goggles. Safety glasses. Ensure eye bath is to hand.

Skin protection: Chemical resistant protective clothing according to DIN EN13034 (Type 6)

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Paraffinic

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: No data available.

Kinematic viscosity: <7mm²/s@40

Boiling point/range°C: 100-125

Melting point/range°C: < -20

Flammability limits %: lower: 0.8

upper: 6.8

Flash point°C: -7

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >220

Vapour pressure: <31hPa@20C

Relative density: 0.730

pH: No data available.

VOC g/l: No data available.

[cont...]

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

[cont...]

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 7

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3295

14.2. UN proper shipping name

Shipping name: HYDROCARBONS, LIQUID, N.O.S.
(HYDROCARBONS,C7-C9,N-ALKANES,ISOALKANES,CYCLICS)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

[cont...]

SAFETY DATA SHEET

PANELWIPE 3 (SLOW)

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.