Technical information Hesse EAZYPORE-WATER WTEP (color tone)



Product description

EAZYPORE-WATER - The innovative solution to striking emphasis of the pores.

Try **EAZYPORE-WATER** to experience the next generation in the refinement of wood. This unique, water-based product is easy to use and can be removed from the surface **without residues**, leaving your wood surface with an impressive depth and structure

EAZYPORE-WATER is specifically developed to accentuate the wood's natural pores – without altering the surface. It merely emphasizes the pores, which results in a striking appearance with high contrast. This technology brings out the grain and texture of the wood to optimal effect, which gives your projects an elegant and sophisticated look.

Whether on furniture, wall cladding or other woodwork – EAZYPORE-WATER is the ideal choice for everyone who wants to adorn their wood surfaces with a special character.

This product is available in classic white and black.

Areas of application

The areas of application could include all interior fittings, furniture making and the coating of parquet – with subsequent top coating.

Area of application

- Internal fit-out
- Kitchen and bathroom
- Furniture

- Crafted parquet flooring
- Industrial parquet flooring
- The fitting out of ship interiors
- Doors
- Stairs

Substrate material

- dark deciduous woods with coarse pores
- light deciduous woods with coarse pores
- suitably pre-primed

Surface Preparation

Surface preparation

The wood must be dry, dust-free and grease-free.

The effect is especially distinctive after the pores are brushed out vigorously.

Application

Application	Spray nozzle size	Spray pressure	Atomizing pressure
Gauze pads / cloth			

Times

Drying	2 h / 20 °C	
--------	-------------	--

Finishing

Finishing Recoating with suitable aqueous or solvent-based Hesse lacquers is necessary.

For more information on Order information, please visit our website, contact our account managers and field service representatives, or contact your specialist dealers.

Technical information Hesse EAZYPORE-WATER WTEP (color tone)



Processing instructions

Apply EAZYPORE-WATER generously in the spraying process or using a brush. Any excess should be uniformly removed first across then with the grain using a gauze bale. This Pore stain is ideally applied on surfaces with a basecoat. The stain can also be applied directly onto the wood if careful wood sanding has been performed prior to coating. It is however more difficult to remove the product without a basecoat. The Pore stain must be removed while it is still moist. Once the stain has dried, the basecoat or the bare wood should be gently sanded before adding the top coat.

Technical data

Flow time (+/- 15%)	70 s / DIN8
NfA	37.9 %
VOC EU	3.15 %
VOC FR	A+
conditions of transport	10 - 30 °C
Shelf life in weeks	<u>⑥</u> 52

Ordering information

Order number	Colour tone	Gloss level
WTEP 700	WEISS	
WTEP 900	SCHWARZ	

General instructions on workmanship

Trial staining of the original sanded wood with original lacquering should be carried out under real conditions. Only use stains from one batch for any one job. Do not pour soiled stains back into the original container. Clean tools with water immediately after use. Dried-on stain residue can be removed with thinners such as ZD 82.

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at www.hesse-lignal.de or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Material safety data sheet is provided in accordance with EC regulation no. 1907/2006.

For more information on Order information, please visit our website, contact our account managers and field service representatives, or contact your specialist dealers.